


Engineer: Bruce Page	Date: 10/12/04	 JPS Communications 5800 Departure Drive, Raleigh, NC 27616			
Drawn: Bruce Page	Date: 10/12//04				
Approved: Chris Samios	Date: 10/12/04	Title: ACU RADIO APPLICATION NOTES			
Issued/ Revised	Date: 10/12/04	Size: A	Dwg. #: 5961-271285-APP	Rev: A	Sheet: 1 Of 1

APPLIES TO: ICOM F3GS Portable Radios
ICOM F4GT Portable Radios

RADIO MODIFICATIONS: None required.

RADIO PROGRAMMING: Not required

RADIO CONTROLS:

1. Adjust the Volume Control until the yellow “SIGNAL” indicator on the associated DSP Module flashes with receive audio. Should be about in the 75% of full volume position.

CABLING:

Standard ACU-1000 and ACU-T Interface cables are made up of a 2 foot TRP Radio Tray Interface cable and the appropriate 13-foot Extension cable.

ACU-1000 Interface Cable	JPS P/N 5961-291285	(5961-271285 + 5961-261002-00)
ACU-T Cable	JPS P/N 5961-281285	(5961-271285 + 5961-281013-00)
TRP-1000 Shelf Interface Cable	JPS P/N 5961-271285	
RF Connector Type		

DSP-1 JUMPERS:

JP1	Low Impedance *
JP2	Balanced *

DSP PROGRAMMING:



RX Level	3*	0dBm*
TX Level	6*	0dBm*
Squelch Type	VOX*	
COR Polarity	Active Low*	
High Frequency Equalizer	4*	Flat*
RX Audio Delay	2*	100 ms*
TX Audio Delay (Radio Type)	0*	No Delay*
Noise Reduction Value	0*	Off*
VOX/VMR Threshold	1*	Med1*
VOX/VMR Hang Time	3*	775 ms*
COR Inhibit After PTT	1*	100 ms*
All Others	As needed	

(* Indicates Default Value)

NOTES:

PURCHASED PART

Rev	ECO	Date
A		10-13-04



USED WITH:
ICOM F3GS PORTABLE RADIOS
ICOM F4GT PORTABLE RADIOS

COMPONENT PCB
(JPS P/N 5961-271000)

C1 JPS P/N 0321-220250
R3 JPS P/N 1820-100000
R6 JPS P/N 1820-152000
JU2
JU4
JU5

NOTES: SHIELD DRAIN CONNECTED TO PIN 1 OF P1 ONLY.

FOR DETAILED CABLE ASSEMBLY INSTRUCTIONS SEE
5961-271001-CBL.

Designed By: RBP	Raytheon JPS Communications		
Drawn By: RBP	Title CABLE, CPC TO ICOM F3GS / F4GT		
Checked By: JAC	Size A	Document Number 5961-271285	Rev A
Issued Date		October 12, 2004	Sheet <u>1</u> of <u>1</u>

PURCHASED PART

Rev	ECO	Date
A		



- NOTES: 1) USE BELDEN 9934 SHIELDED CABLE.
2) CONNECT SHIELD DRAIN TO SHELL OF P1 ONLY.
3) CONNECTORS P1 AND P2 MUST BE MOLDED TO THE CABLE.
4) CABLE MUST BE LABELED WITH THE RAYTHEON/JPS P/N AND REV, VENDOR CODE AND DATE (MM/YY).


Designed By: JAC	Raytheon JPS Communications		
Drawn By: JAC	Title CABLE, ACU-1000 RADIO EXTENSION - 13 FT		
Checked By: RBP	Size A	Document Number 5961-261002-00	Rev A
Issued Date JANUARY 5, 2004		Sheet <u>1</u> of <u>1</u>	

Rev	ECO	Date
A		

PURCHASED PART

CONNECTOR AMP P/N 206708-1
(JPS P/N 0362-005003)
FEMALE PIN AMP P/N 1-66105-8
(JPS P/N 0362-005002)

CONNECTOR AMP P/N 206705-4
(JPS P/N 0362-009001)
MALE PIN AMP P/N 1-66103-7
(JPS P/N 0847-000011)



- NOTES: 1) USE BELDEN 9934 SHIELDED CABLE.
2) CONNECT SHIELD DRAIN TO PIN 1 OF P1 ONLY.
3) CONNECTORS P1 AND P2 MUST BE MOLDED TO THE CABLE.
4) CABLE MUST BE LABELED WITH THE RAYTHEON/JPS P/N AND REV, VENDOR CODE AND DATE (MM/YY).

Designed By: JAC	Raytheon JPS Communications Raleigh, NC USA		
Drawn By: JAC	Title CABLE, ACU-T RADIO EXTENSION - 13 FT		
Checked By: RBP	Size A	Document Number 5961-281013-00	Rev A
Issued Date JANUARY 5, 2004		Sheet <u>1</u> of <u>1</u>	